



## DB-5 BRIDGE PLUG

### PRODUCT 20-502

The DB-5 Bridge Plug is an economical, fully drillable Bridge Plug for applications where a 35MPa (5,000 PSI) plug is sufficient. The DB-5 is suitable for well abandonment or zone suspensions.

This Bridge Plug is designed for running and setting using an E-4 Pressure Setting Assembly, or on regular or coiled tubing using a B Hydraulic Setting Assembly.

The DB-5 features one piece full circle type slips that will set securely in up to P-110 grade casing, while still maintaining good and consistent drill out times.

The DB-5 Bridge Plug is rated for continuous service at 35MPa (5,000 PSI) differential pressure at 94°C (200°F).



CASING SIZE	CASING WEIGHT		PRODUCT NUMBER	RUNNING O.D.	EUE THREAD	PRESSURE	TUBING TENSION
	IN/MM	LBS/FT		KG/M	IN/MM		IN/MM
4 1/2 114.3	9.5 - 16.6	14.0 - 24.7	20-505-0450	3.6	2 3/8	1,500 10,000	25,000 11,100
			20-506-0450	91.4	60.3		
5 1/2 139.7	13.0 - 23.0	19.0 - 34.2	20-505-0550	4.24	2 3/8		
			20-506-0550	107.7	60.3		
7 177.8	17.0 - 35.0	25.0 - 52.1	20-505-0700	5.61	2 7/8		45,000 20,000
			20-506-0700	142.3	73.0		